

iBR iTC S3 CLCS







Reboarding platform



Flowing edge design



Hinged seat



Ski tow hook



Quick latch fuel filler design

Specifications

139" / 354 cm
48" / 122 cm
45.9" / 116.6 cm
845 lb. / 383 kg
3
15.9 US gal / 60 l
13.7 US gal / 52 I

ENGINE	
Туре	1503 XHO Rotax® 4-TEC® engine*
Intake system	Supercharged with intercooler, 60 mm throttle body
Bore x stroke	100 mm x 63.4 mm
Displacement	1,494 cc
Compression ratio	8.4:1
Cooling	Closed-loop cooling system (CLCS)
Fuel type	87 octane — minimum 91 octane — recommended

DRIVE UNIT	
Propulsion system	.Sea-Doo® Direct Drive
Jet pump	.Aluminium, axial flow, single stage, large hub with 10-vane stator
Transmission	.iBR™
Impeller	.Stainless steel

Impeller	Stainless steel
ELECTRICAL	
IgnitionStarterBattery	Electric
HULL AND COMPONENTS	
TypeColour	

Standard Features

Stanuaru Features				
HULL AND COMPONENTS	S			
iControl™	The "Brain" that integrates and controls all			
S³ Hull	systems to create the best possible rideStepped, stable & strong. Lightweight material, ribbed and stepped. Creates a low-pressure zone to reduce			
Touring / Sport mode	drag for nimble handling and rail-tight corneringOffers a choice between two throttle responses for different riding styles. Touring mode is the default setting offering a more progressive acceleration curve for a more confident ride — ideal for cruising			
Hinged seat	and 2-up riding. Sport mode can be easily activated using the Set button. It provides all acceleration performance for a more aggressive throttle responseEasy-open seat with convenient stay-open support struts. Provides easy access to the engine compartment while remaining attached to the watercraft.			
Watertight, removable	Provides dry storage for luggage and necessities			
storage bin	with easy access.			
Tilt steering	4 adjustable steering and information centre angles for maximum ease and comfort.			
Fold-down reboarding ste	pMakes reboarding from the water easier and quicker.			
Bow and stern eyes	Designed for towing or securing the craft to a trailer or dock.			
Carpeted footwells	Offer extra comfort, non-skid surface and			
and deck pads	great looks.			
Ski tow eye	For easy and secure attachment of ski rope.			
Information Centre	Fuel level, Tachometer, Speedometer, Hour meter, Compass, Clock, Fuel consumption meter, Water temperature, Touring / Sport mode, Cruise control, Slow mode, VTS™, F-N-R indicator, Low fuel level, Low oil level, Low oil pressure, Low voltage, Overheat, Hi voltage, Check engine, Sensor check, Battery protection, Key (wrong key), L-Key / R-Key, Maintenance info, Error codes.			
D: 11 II II II II 11 11				

System (D.E.S.S.™) System (VTS)

Digitally Encoded Security....Industry's first digitally encoded theft-deterrent system.

and booklet

Electric Variable TrimProvides boat trim adjustments, maximises acceleration and high-speed stability. Foam flotationRide with security and peace of mind. Meets or exceeds USCG standards.

Off-Throttle Assisted Steering (0.T.A.S.[™])

Quick latch fuel filler design

.Provides the operator with additional steering effect in off-throttle situations for greater manoeuvrability.

Sponsons **Bumpers** Adjustable mirrors Reboarding platform Reboarding handles on rear platform Rear grab handle Front splash deflector

Dual drain plugs External exhaust cooling flush attachment Special comfort hand grips Emergency floating lanvard Cut & sew seat with multi colours Seat strap Operator's guide, instructional video

OPTIONS

3-position retractable ski pylon Removable wakeboard rack Depth finder Ski mode Time/distance to empty Altitude Top/average speed/RPM Lap timer

Removable dry bag for front storage Glove box organiser Safety kit Sandbag anchor Speed Tie Protective cover Advanced TEC trailer Fire extinguisher

WARRANTY

Engine temperature

BRP limited warranty covers the watercraft for one year.*





*In some markets, the duration of the warranty coverage may differ

RXT 260 RS



ENGINE

Supercharged, intercooled 1,494 cc four-stroke, Rotax with four valves per cylinder iTC™ (Intelligent Throttle Control) system

....Supercharged, intercooled 1503 XHO Rotax 4-TEC engine provides reliable ultra-high performance in fresh or saltwater, increased torque at low RPM, optimised power at all RPM levels and throttle positions. . Operating electronically, this advanced throttle system starts you in neutral for easier dockside starts. It also features an activity-specific cruise control, Touring / Sport mode and Variable Trim System that can all be set to accommodate your riding style. The result is a more responsive, more intuitive ride.

iControl Learning Key[™].......The programmable Learning Key allows you to limit the performance of the PWC based on rider skill-level. Each of the two settings can be fine-tuned using the mode/set buttons.

Multi-port fuel injection Better control of exhaust emission and power at all RPM ranges to reduce emissions and reduce fuel consumption.

D-Sea-Bel[™] system..... . Combines a series of resonators and vibrationabsorbing components to make Sea-Doo watercraft some of the quietest on the water.

Water-cooled exhaust pipe ... Regulates exhaust temperature.

Closed-loop cooling system.. Uses coolant to keep the engine running at the ideal temperature, much like a car's radiator. Also keeps

out corrosive saltwater and debris. Water/air separator......Provides maximum airflow to engine and reduces

water intrusion.

Watertight digital ignition.... Provides optimal energy for a consistent spark, ensuring maximum performance.

RPM limiter Protects engine from over-revving. Warning device......Warns operator of engine and exhaust overheating,

engine management and system failure. Handlebar-mounted......Engine starts and stops with single, start/stop button user-friendly control button. Tip Over Protection Protects engine in case of turn over.

PROPULSION SYSTEM

System (T.O.P.S.™)

iBR (Intelligent Brake	.The world's only on-water braking system, iBR lets you
& Reverse) system	stop up to 100 feet sooner than any other watercraft ¹ .
	All with the squeeze of a lever. And with its electronic
	reverse, it gives you a level of maneuverability that
	makes docking easier.
Sea-Doo Direct Drive	Delivers optimum performance with the Rotax
propulsion system	engine.
Aluminium stator vanes	. Handles the high-performance engine without erosion.
Replaceable UHMW**	Provides long impeller life, less maintenance
wear ring	and maximum thrust.
Dual automatic vacuum	. Continuously removes water entering the
siphon pumps	engine compartment.
Large diameter drive shaft	.Maintains engine and pump alignment at all
with crowned spline design	operating speeds.
Stainless steel	Delivers improved acceleration, higher top
impeller	speed and less cavitation.



