



T³ HULL™



ADJUSTABLE REAR SPONSONS



ERGOLOCK SYSTEM



TRIM TABS

2015 PERFORMANCE RXP-X 260

The ultimate in power and control. It pushes the limits of what's possible in race riding. Through agility, power, sharp handling, precise cornering and innovative design. And its exclusive Ergolock system reduces fatigue and keeps your upper body more relaxed as you lock your legs into the narrow seat to become one with the watercraft.



NEW Sunburst Yellow & Hyper Silver

RIDER CAPACITY



Weight capacity..... 400 lb / 182 kg

DIMENSIONS

Fuel capacity..... 15.9 gal / 60 l
 Length..... 130.6" / 331.6 cm
 Width 48.3" / 122.7 cm
 Weight (dry)..... 835 lb / 378.7 kg
 Storage capacity 30.7 gal / 116.4 l

HULL

Type..... T³
 • Medium-sized platform
 • Rough water inspired deep-V hull
 • Better lean-in and precise cornering

ENGINE

Type..... 1503 HO Rotax 4-TEC® engine
 Intake system..... Supercharged with external intercooler
 Displacement..... 1,494 cc
 Cooling..... Closed-Loop Cooling System (CLCS)
 Reverse system iBR® with electronic brake, neutral and reverse
 Starter..... Electric
 Fuel type 87 octane – minimum
 91 octane – recommended



ADJUSTABLE ERGONOMIC STEERING (A.E.S.™)



SEA-DOO® SPEED TIE™ (OPTION)

RXP-X 260



ENGINE

| | |
|---|---|
| 1,494 cc four-stroke, Rotax with four valves per cylinder | Supercharged, external intercooled 1503 HO Rotax 4-TEC engine provides reliable ultra-high performance in fresh or salt water, increased torque at low RPM, optimized power at all RPM levels and throttle positions. |
| iTC™ (Intelligent Throttle Control) system | Operating electronically, this advanced throttle system starts you in neutral for easier dockside starts. It also features an activity-specific Touring, Sport and ECO™ modes that can all be set to accommodate your riding style. The result is a more responsive, more intuitive ride. |
| iControl® Learning Key® | The programmable Learning Key allows you to limit the performance of the PWC based on rider skill level. |
| D-Sea-Bel™ system | Combines a series of resonators and vibration-absorbing components to make Sea-Doo watercraft some of the quietest on the water. |
| Closed-Loop Cooling System | Uses coolant to keep the engine running at the ideal temperature, much like a car's radiator. Also keeps out corrosive saltwater and debris. |
| Handlebar-mounted start/stop button | Engine starts and stops with single, user-friendly control button. |

FEATURES

| | |
|---|--|
| iControl | The "Brain" that integrates and controls all systems to create the best possible ride. |
| T ³ Hull | Innovative multi-staged design with extreme hard and soft chines. Allows for more precise cornering, enhances lean-in, cuts water and tracks better; extremely responsive. |
| Ergolock system | Combination of ergonomic features allow amazing control while cornering with less upper body fatigue. It features a narrow racing seat with knee grab design, adjustable handlebars and angled footwells that allow you to "lock" in when cornering hard. This results in faster turns and more time on the water. |
| Trim tabs | Limit bow rise and improve parallelism to water. Also increase tracking in rough water conditions. |
| High-performance electric VTS™ (Variable Trim System) | Provides pre-set positions for quick settings when adjusting boat trim, maximizes acceleration and high-speed stability. |
| ECO mode | The iTC function that automatically determines the most economical power delivery and sets the optimal RPM for greatest fuel economy. |
| Interactive Multifunction Digital Information Center | Reports 29 key operating functions: Fuel level, Tachometer, Speedometer, Hour meter, Compass, Clock, Fuel consumption instant & average, Touring mode, Sport mode, ECO mode, VTS preset, F-N-R indicator and more. |
| RF D.E.S.S.™ Key | Now with radio frequency technology and a new ball-and-socket design, the new Digitally Encoded Security System (D.E.S.S.) key provides riders with easy and quick starts every time. |
| Off-Throttle Assisted Steering (O.T.A.S.™) | Provides the operator with additional steering effect in off-throttle situations for greater maneuverability. |
| 2-up seat | Tow hook |
| Elevated fuel filler | Dual drain plugs |
| Bumpers | Flush kit |
| Wide-angle mirrors | Emergency floating lanyard |
| Footwell carpets with Sea-Doo pattern | Seat strap |
| Swim platform carpet with Sea-Doo logo | Operator's guide, instructional video and booklet |
| Rear grab handle | |

PROPULSION SYSTEM

| | |
|--|---|
| iBR (Intelligent Brake & Reverse) system | Sea-Doo's exclusive on-water braking system, iBR lets you stop up to 100 feet sooner than competitive units! All with the squeeze of a lever. And with its electronic reverse, it gives you a level of maneuverability that makes docking easier. |
| Stainless steel impeller | Delivers improved acceleration, higher top speed and less cavitation. |

X-PACKAGE

| | |
|--|--|
| X-Coloration seat | Race-inspired design for comfort and great looks. |
| X-Handlebars with A.E.S. (Adjustable Ergonomic Steering) | The only fully adjustable handlebar in the industry. With A.E.S. the rider can adjust the handlebar width and grip angle for a fully customized ride. |
| X-Gauge with boost indicator | Shows the boost pressure in real-time from minimum (idle) to max boost pressure (open throttle) at all times so the rider knows the engine load condition. |
| Adjustable rear sponsons | An efficient design that improves lateral stability. 3-position adjustable for your skill level and riding environment: higher for a more playful freeride experience or lower for more aggressive turning. Winglet feature enhances lean angles during turning. |
| Additional gauge functions | Time / Distance to empty, Top / average speed / RPM, Lap timer, Engine temperature. |

OPTIONS

- Slow mode
- Cruise control
- Depth finder
- Speed Tie
- Fold-down reboarding step
- Removable dry bag for front storage
- Sandbag anchor
- Safety kit
- Bilge pump
- Fire extinguisher
- Fender
- Sea-Doo Move trailer
- Storage cover

WARRANTY

BRP limited warranty covers the watercraft for one year.

